

PRODUCT AWARENESS BULLETIN

FROM ROSENBAUER

BULLETIN NUMBER: 3044

QUOTE WRITER NUMBER: SPECIAL

DATE: 5-20-09

TRUCK: 14701 - WINTHROP, WA

THIS BULLETIN INCLUDES INFORMATION ABOUT A NEW OR EXISTING OPTION OR FEATURE THAT IS AVAILABLE FOR PRODUCTION.

DESCRIPTION: Speedlay/Storage Assembly

PLANT: Rosenbauer

SPECIFICATION: A 1 $\frac{3}{4}$ " pre-connect hose speedlay shall be installed behind the chassis cab, controlled with quarter turn 2" diameter ball valve. The outlet shall be equipped 2" NPT female swivel x 1 $\frac{1}{2}$ " male NST hose threads. The hosebed decking shall be constructed with slots integrated into the hosebed floor. The single stack hosebed shall provide a minimum capacity of 200 feet of 1 $\frac{3}{4}$ " diameter double jacket hose with hose and nozzle provided by fire department.

A transverse storage compartment shall be provided above the speedlay. The compartment shall be equipped with a hinged door on each side. Each door shall be equipped with a push button latch.

As this photo shows, the whole assembly can be coated with a black thermoplastic material. This is available as an additional option.

