

PRODUCT AWARENESS BULLETIN

FROM ROSENBAUER

BULLETIN NUMBER: 3050

QUOTE WRITER NUMBER: SEE BELOW

DATE: 9-30-09

THIS BULLETIN INCLUDES INFORMATION ABOUT A NEW OR EXISTING OPTION OR FEATURE THAT IS AVAILABLE FOR PRODUCTION.

DESCRIPTION: Running Change - Powder Coated EZ Slide-Out Tray

PLANT: Rosenbauer

SPECIFICATION: A roll-out equipment tray shall be installed in the compartment. The tray with telescoping slides and cam follower bearings shall be rated to a maximum load of 250 lbs. The tray shall have a gas shock to hold the tray extended or closed. There shall be a lock to prevent movement, when the tray is in the closed position. The tray's slide mechanism shall be powder coated.

The tray shall be of a closed-in design, formed of .188" smooth aluminum plate, fabricated with two (2) inch sides. Trim-Lok edge trim shall be installed on the front lip to afford protection to equipment and firefighter when loading/unloading. Reflective material measuring 1" x 6" shall be installed on each front corner both on the face and side of tray for firefighter safety.

The tray unit shall roll out of the compartment, with latching mechanism to hold tray in and stored positions.



45-05-1100: 250# 1/8 Aluminum

45-05-3100: 250# 3/16 Aluminum

45-06-1100: 500# 3/16 Aluminum