

PRODUCT AWARENESS BULLETIN FROM ROSENBAUER

Bulletin No. 6002C
Quote Writer No: 62-02-4100
Date: 4-27-07

THIS BULLETIN INCLUDES INFORMATION ABOUT A NEW OR EXISTING OPTION OR FEATURE THAT IS AVAILABLE FOR PRODUCTION

DESCRIPTION: Handrail w/Telescoping Light

PLANT: Central

SPECIFICATION: A Fire Research Optimum model OPA540-S50 side mount pull up telescopic light shall be installed. The light pole shall be anodized aluminum and have a knurled twist lock mechanism to secure the extension pole in position. The extension pole shall rotate 360 degrees. An internal brake shall slow the extension pole during lowering. The outer pole shall be a grooved aluminum extrusion and qualify as an NFPA compliant handrail. The pole mounting brackets shall have a 2 3/4" offset. Wiring shall extend from the pole bottom with a 4' retractile cord.

The lamphead shall have one (1) quartz halogen 500 watt 120 volt bulb. The bulb will draw 4.2 amps and generate 10,500 lumens. The bulb shall be accessible through the front. The lamphead shall incorporate a vacuum deposit polished reflector and two optimizing mirrors to produce a uniform beam that lights up an area 100° vertically by 150° horizontally. The lamphead shall have a heat dissipating curved front lens. The curve of the lens shall have a radius of 5.16 inches to optimize light emission. The lamphead shall be no more than 4 3/4" deep by 5 1/8" high by 8 3/4" wide. Lamphead and brackets shall be powder coated white.

62-02-4000 FRC Optimum Telescopic - Top Raise
62-02-4100 Opti, 500W-120V, Top Raise-Sde Mnt
62-02-4200 Opti, 750W-120V, Top Raise-Sde Mnt
62-02-4300 Opti, 1500W-240V, Top Raise-Sde Mnt

62-02-5000 FRC Focus Telescopic - Top Raise
62-02-5100 Focus, 500W-120V, Top Raise-Sde Mnt
62-02-5200 Focus, 750W-120V, Top Raise-Sde Mnt
62-02-5300 Focus, 1500W-240V, Top Raise-Sde Mnt

62-02-6000 FRC NightMaster Telescopic - Top Raise
62-02-6100 N/Mstr, 500W-120V, Top Raise-Sde Mnt
62-02-6200 N/Mstr, 1000W-120V, Top Raise-Sde Mnt
62-02-6300 N/Mstr, 1500W-240V, Top Raise-Sde Mnt

